

MODEL MILANO STONE 2.0

Chimney stove for solid fuels without hot water supply DIN EN 13240:2001/A2:2004/AC:2007

European Standard DIN EN 13240 I Test Report N°: P8-017/2012 + 40 12 2953 - 2013/07/01 I Test Centre ID: 1004 + 1625

Purpose and description of chimney stove

- | | |
|--|---|
| <input type="checkbox"/> Chimney stove for solid fuels (split logs) without hot water supply | <input type="checkbox"/> Operation independent from ambient air possible |
| <input type="checkbox"/> 6 kW nominal heat output | <input type="checkbox"/> Flue connection possible on top or at rear |
| <input type="checkbox"/> Connection for external combustion air supply available | <input type="checkbox"/> Proper wood stove / not suited for coal briquettes |
| <input type="checkbox"/> Heat storage stones available as an option | <input type="checkbox"/> Unit does neither have shaking grate nor ash box |
| <input type="checkbox"/> Available in soapstone | <input type="checkbox"/> Shared chimney flues admissible |
| | <input type="checkbox"/> This stove is not a low burning stove! |

Solid Fuel Fireplaces I Directive Mandate 89.106.EEC

Manufacturer: skantherm GmbH & Co. KG, Country: (Abbreviation) D (in full) Federal Republic of Germany

Address: Von-Büren-Allee 16, 59302 Oelde, Tel. +49(0) 25 22-59 01-0, Fax +49(0) 25 22-59 01-149, Email: info@skantherm.de

If the Declaration of Conformity is issued by an authorized representative domiciled in the EEA (European Economic Area):

Authorised Representative: Mr Benedikt Wagner, Country: (Abbreviation) D (in full) Federal Republic of Germany

Address: Von-Büren-Allee 16, 59302 Oelde, Tel. +49(0) 25 22-59 01-0, Fax +49(0) 25 22-59 01-149, Email: info@skantherm.de

The notified test laboratory Rhein-Ruhr-Feurstättenprüfstelle GmbH, No. 1625 and Fraunhofer Institut Bauphysik, No: 1004 have executed the initial testing according to system 3 and documented it in the test report P8-017/2012 + RRF - 40 12 2953.

Harmonized technical specification	DIN EN 13240:2001/A2:2004/AC:2007
Essential characteristics	Performance
Fire safety	
Reaction to fire	A1
Distance to combustible materials	Minimum distances, in mm rear = 250 sides = 350 front = 1000
Risk of burning fuel falling out	Pass
Emission of combustion products	CO [≤ 0.10 %]
Surface temperature	Pass
Electrical safety	-
Cleanability	Pass
Maximum water operating pressure	- bar
Flue gas temperature at nominal heat output	T [253 °C]
Mechanical resistance (to carry a chimney/flue)	NPD
Thermal output	
Nominal heat output	6 kW
Room heating output	6 kW
Water heating output	- kW
Energy efficiency	$\eta \geq 73.0$ %]

The performance of the product mentioned above corresponds to the data mentioned above.

Only the manufacturer is responsible for the creation of this declaration of performance.

Name: Benedikt Wagner

(identification of person authorized to legally sign on behalf of manufacturer or his duly authorized representative)

Signature and Title:
(or equivalent signature)


Managing Director
Date: [DD/MM/YY] 16/11/17